

HYDRONIC RADIANT CENTER H SERIES • IN-FLOOR HEATING SYSTEM

When getting it done quickly and correctly is big on your mind!

- Compact Size
- Flexible with sizes from 7 to 27 kW
- Reliable operation
- Pressure tested to eliminate call backs
- Modulating element operation
- Low resistance to flow
- Redundant safety features
- Digital read out for flow, temperatures
- Field programmable advanced read out features
- CSA, UL and ASME listed
- Can be shipped UPS, Speedee or FedEx ground



For your comfort and savings.



TTHERM.COM or TTHERMSTORE.COM

P: 507-463-3213
F: 507-463-3215
13128 240th Ave.
New Richland, MN 56072



TERRA-THERM INC.

HYDRONIC RADIANT CENTER H SERIES • IN-FLOOR HEATING SYSTEM

SIX EASY STEPS:

1. Mount the HRC Panel on the wall (24" x 32")
2. Install the Hubbell Electric Tankless Heater & Bladder Tank
3. Connect to the radiant floor manifold system
4. Wire the Hubbell Electric Heater, Pump & Thermostat
5. Flush, Fill & Purge then add Antifreeze
6. Turn it on and enjoy warm radiant floors!

Hydronic Radiant Center Includes:

- Hubbell Electric Tankless Heater
- Circulating Pump
- Bladder Tank
- Pressure Gauge
- Air Bleed
- Melamine Panel
- Isolator Flange™ (Fill and Purge Valve)
- Factory Leak-Tested
- Shipped in three separate cartons:
 - Panel with components
 - Hubbell Electric Tankless Heater
 - Bladder Tank



Model Number	Output @ 240 VAC (kW)	Capacity (BTUH)	Breaker Size (Amps)	Heater Size (Amps)	Panel Size
HHRC-7	7	23,890	30	29	24" x 32"
HHRC-9	9	30,710	40	37.5	24" x 32"
HHRC-11	11	37,540	50	46	24" x 32"
HHRC-14	14	47,780	60	58	24" x 32"
HHRC-21	21	71,670	90	87	24" x 32"
HHRC-27*	27	92,150	120	112	24" x 32"

* Also available in 3 phase



THERM.COM or **THERMSTORE.COM**

P: 507-463-3213

F: 507-463-3215

13128 240th Ave.

New Richland, MN 56072

© 2012 Terra-Therm Inc. HH01-12H



TERRA-THERM INC.