

# HYDRONIC RADIANT CENTER S SERIES • IN-FLOOR HEATING SYSTEM

When getting it done quickly and correctly is big on your mind!

- Compact Size
- Flexible with sizes from 7 to 22 kW
- Reliable operation
- Pressure tested to eliminate call backs
- Modulating element operation
- Low resistance to flow
- Redundant safety features
- CSA and UL listed
- Can be shipped UPS, SpeedDee or FedEx ground



For your comfort and savings.



[TTHERM.COM](http://TTHERM.COM) or [TTHERMSTORE.COM](http://TTHERMSTORE.COM)

P: 507-463-3213  
F: 507-463-3215  
13128 240th Ave.  
New Richland, MN 56072



**TERRA-THERM INC.**

# HYDRONIC RADIANT CENTER S SERIES • IN-FLOOR HEATING SYSTEM

## FIVE EASY STEPS:

1. Mount the HRC Panel on the wall
2. Connect to the radiant floor manifold system
3. Wire the Electric Tankless Heater, Pump & Thermostat
4. Fill, Purge then add Antifreeze
5. Turn it on and enjoy warm radiant floors

### Hydronic Radiant Center Includes:

- SEISCO Electric Tankless Heater
- Circulating Pump (2 sizes)
- Bladder Tank (2 sizes)
- Pressure/Temperature Gauge
- Air Bleed
- Melamine Panel
- Isolator Flange™ (Fill and Purge Valve)
- Factory Leak-Tested
- Shipped in two separate cartons:
  - Panel with components & heater
  - Bladder Tank

Model Number	Output @ 240 VAC (kW)	Capacity (BTUH)	Breaker Size (Amps)	Heater Size (Amps)	Panel Size
HRC-1542-7	7	23,890	40	29	24" X 24"
HRC-2699-7	7	23,890	40	29	24" X 24"
HRC1542-9	9	30,710	50	38	24" X 24"
HRC2699-9	9	30,710	50	38	24" X 24"
HRC1542-11	11	37,540	60	46	24" X 24"
HRC2699-11	11	37,540	60	46	24" X 24"
HRC2699-14	14	47,780	80	59	24" X 32"
HRC2699-18	18	61,430	100	75	24" X 32"
HRC2699-22	22	75,080	120	92	24" X 32"

**New & Improved!**  
Now with  
Isolator Flange™

